



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number:

0 457 427 A2

12

EUROPEAN PATENT APPLICATION

21 Application number: 91302943.5

51 Int. Cl.⁵: H04N 1/46

22 Date of filing: 04.04.91

30 Priority: 26.04.90 IL 94215
03.07.90 IL 94956

43 Date of publication of application:
21.11.91 Bulletin 91/47

64 Designated Contracting States:
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

71 Applicant: SCITEX CORPORATION LTD.
7 Hamada Street
Herzliya 46103(IL)


72 Inventor: Nagler, Michael
27 Ben Yoseph Street
Ramat Aviv Gimmel 69 125(IL)
Inventor: Melman, Haim Zvi
3 Hagai Street
Kfar Sava 44 472(IL)

74 Representative: Hillier, Peter
Reginald W. Barker & Co., 13, Charterhouse
Square
London, EC1M 6BA(GB)

54 Apparatus for sharpening a colour image.

57 An apparatus for sharpening a color image having a multiplicity of color separation signals defining a plurality of color pixels comprising apparatus for generating at least two sharpening signals from the

color separation signals and apparatus for combining each of the color separation signals with any collection of the at least two sharpening signals wherein the collection changes throughout the color image.



EP 0 457 427 A2

FIELD OF THE INVENTION

The present invention relates to detail enhancement of color images generally.

BACKGROUND OF THE INVENTION

Analog and digital detail enhancement, known as "unsharp masking", is well known and widely used in the graphic arts, as well as in other fields. It is used to produce sharp printed reproductions from original images by enhancing the color density differences at edges between areas of different color and is discussed in the following publications:

Jackson, Lonnie L., "Unsharp Masking: Photographic/Electronic," Gatfworld, May-June 1989, Vol. 1, pp. 13 - 22;

Molla, R.K., Electronic Color Separation, R.K. Printing & Publishing Co., Montgomery, W. Virginia, 1988, pp. 230 - 232; and

U.S. Patent 4,335,407 to Atoji et al.

Two methods are used for detail enhancement, the utilization of a single color channel to produce a single detail enhancement signal for each of three or four color channels or for each of the three or four printers and the utilization of each color channel to produce a separate detail enhancement signal per channel. These two methods can be implemented in both analog and digital systems, such as color separation scanners.

The first method adds to the enhanced edges a generally gray line, making the edge of a color area appear to be more gray. This effect, often referred to as "contours", is undesirable for most graphic arts applications.

The second method adds a color enhancing line to the edge of a color area, thereby generally enhancing the color separation of the area at the edge to more sharply define the color edge. This effect is desirable and produces printed images of high quality.

The two methods have their advantages and disadvantages, particularly in regard to color noise. When scanning a color area, many pixels are produced to represent the area and the average color of the pixels in the area is the color of the area. However, due to noise that is inherent in the detection process, an individual pixel will typically have a color which is slightly different from the average color of the area. This effect is known as color noise and is easily detected by the human eye, especially when the average color is gray.

The second method emphasizes this effect by adding a color component to each pixel. On the other hand, the first method adds a gray component to each pixel, thereby reducing the color separation in the pixel and consequently, reducing the color noise.

At the edges between gray areas, where typically the Red, Green and Blue components of each gray color are essentially of the same color, both methods provide a sharpening line of the same average color and are, therefore, equivalent. The second method, however, will increase any color noise in the gray areas and the first method will reduce it.

From the above discussion, it is clear that neither method is superior than the other in all situations. The desirability of each method depends on the colors in the image.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide an apparatus and method for sharpening a color image which utilizes more than one method of detail enhancement for reproduction of any original image.

There is therefore provided, in accordance with a preferred embodiment of the present invention, an apparatus for sharpening a color image having a multiplicity of color separation signals defining a plurality of color pixels comprising apparatus for generating at least two sharpening signals from the color separation signals and apparatus for combining each of the color separation signals with any collection of the at least two sharpening signals wherein the collection changes throughout the color image.

Additionally, in accordance with a preferred embodiment of the present invention, the apparatus for combining includes apparatus for determining the collection as a function of at least one dimension of the at least three dimensional color value of each of the plurality of pixels.

Moreover, in accordance with an alternative embodiment of the present invention, the apparatus for determining includes apparatus for separating a color solid into first, second and third volumes. If the three dimensional color value of a pixel falls within the first volume, a first collection of sharpening signals are combined with the color separation signals. If the three dimensional color value of a pixel falls within the third volume a second collection of sharpening signals are combined with the color separation signals. If the three dimensional color value of a pixel falls within the second volume, located generally between the first and third volumes, a combination of the first and the second collections of sharpening signals are combined with the color separation signals wherein the combination gradually changes from generally the entirety of the first collection to generally the entirety of the second collection.

Further, in accordance with a preferred embodiment of the present invention, the apparatus

for generating includes apparatus for performing edge detection on each of the color separation signals.

Still further, in accordance with a preferred embodiment of the present invention, the color separation signals are in a predetermined color space and the sharpening signals are also in the predetermined color space.

There is additionally provided, in accordance with a preferred embodiment of the present invention, a method of sharpening a color image having a multiplicity of color separation signals defining a plurality of color pixels including the steps of generating at least two sharpening signals from the color separation signals and combining each of the color separation signals with any collection of the at least two sharpening signals wherein the collection changes throughout the color image.

Additionally, in accordance with a preferred embodiment of the present invention, the step of combining includes the step of determining the collection as a function of at least one dimension of the at least three dimensional color value of each of the plurality of pixels.

Moreover, in accordance with an alternative embodiment of the present invention, the step of determining includes the step of separating a color solid into first, second and third volumes. If the three dimensional color value of a pixel falls within the first volume, a first collection of sharpening signals are combined with the color separation signals. If the three dimensional color value of a pixel falls within the third volume a second collection of sharpening signals are combined with the color separation signals. If the three dimensional color value of a pixel falls within the second volume, located generally between the first and third volumes, a combination of the first and the second collections of sharpening signals are combined with the color separation signals wherein the combination gradually changes from generally the entirety of the first collection to generally the entirety of the second collection.

Finally, in accordance with a preferred embodiment of the present invention, the step of generating includes the step of performing edge detection on each of the color separation signals.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

Fig. 1 is a block diagram illustration of a first embodiment of a color sharpening system of the present invention;

Fig. 2 is a block diagram illustration of a second

embodiment of the system of the present invention;

Fig. 3 is a graphic illustration of a Munsell Color Solid useful in the invention of Figs. 1 and 2;

Fig. 4 is a graphic illustration of a division of the Munsell Color Solid of Fig. 3 useful in an alternative embodiment of the invention of Figs. 1 and 2.

DETAILED DESCRIPTION OF PRESENT INVENTION

Reference is made to Fig. 1 which illustrates, in block diagram form, the system for color sharpening of the present invention.

The system comprises a sharp signal generator 10 for receiving Red (R), Green (G) and Blue (B) color separation signals from a color separation source, such as a color separation scanner or a color separation camera, and for producing sharp signals R_s , G_s , and B_s , respectively, for the Red, Green and Blue color separation signals. Alternatively, the color separation signals can be of the Cyan (C), Magenta (M), Yellow (Y) and Black (K) separation, or of any other suitable color separation. In a system receiving the C, Y, M and K color separation signals, the sharp signal generator 10 produces the sharp signals C_s , M_s , Y_s , and H_s . It will be appreciated that the sharp signals are preferably in the same color space as the input color separation signals where, for the following description, the Red, Green and Blue color space will be used.

The system additionally comprises three summers 12, 14 and 16 for receiving a color separation signal from a color separation source, and any or none of sharp signals R_s , G_s or B_s . The color separation signals received by summers 12, 14 and 16 are respectively, the Red (R), Green (G) and Blue (B) color separation signals.

The sharp signals R_s , G_s and B_s are received by summers 12, 14 and 16, via three individually controlled switches 20, 22 and 24, respectively, operative to switch the signals between three positions, A, 0 and S.

When a switch 20, 22 or 24 is in the 0 position, it does not connect the respective sharp signal R_s , G_s or B_s to any of summers 12, 14 or 16. When a switch is in the S position, the respective sharp signal is connected to the summer receiving the respective color separation signal. Finally, when a switch is in the A position, the respective sharp signal is connected to all of the summers 12, 14 and 16. Each collection of position settings of the switches 20, 22 and 24 is called a mode.

The first method described in the Background of the Invention is the mode wherein one of the

switches, typically switch 22 which receives G_s , is set to the A position and the remaining switches 20 and 24 are set to the 0 position. The second method described in the Background of the Invention is the mode wherein each of the switches 20, 22 and 24 is set to the S position.

The switches 20, 22 and 24 are individually operated by a color coordinates computer 30 in accordance with a predefined color criteria. The color criteria define ranges within a three-dimensional color space in which a given mode will be operative. Thus, the color coordinates computer 30 receives the R, G and B color separation signals and, for each pixel, determines where in the three-dimensional color space a given pixel lies. The switch setting for the range within which the given pixel lies will then be implemented.

A typical three-dimensional color space, known as the Munsell Color Solid, is shown in Fig. 3 and marked as reference number 30. It is described on pages 507 - 510 of the book, Color Science: Concepts and Methods, Quantitative Data and Formulae, 2nd Edition, by Gunter Wyszecki and W.S. Stiles and published by John Wiley and Sons, New York, NY in 1982. The vertical axis is the luminance axis, the horizontal plane comprises the polar axes of saturation and hue where saturation is the radial component and hue is the angular component.

A typical, two range color criteria can be defined by intersecting the Munsell Color Solid 30 with a cylinder 32 of radius r_0 along the luminance axis. All pixels falling within the intersection of the Solid 30 and the cylinder 32 are relatively gray pixels for which the first method of the Background of the Invention is operative. All pixels not falling within the intersection of the Solid 30 and the cylinder 32 are non-gray pixels for which the second method of the Background of the Invention is operative.

A second, two range color criteria can be defined by defining a volume with luminance higher than a first threshold and lower than a second threshold.

It will be appreciated that, criteria utilizing the Munsell Color Solid 30 require a transformation of the R, G and B color components of each pixel to luminance, hue and saturation components. Other criteria may be defined which are expressed in the R, G and B color coordinates. If more than two color criteria ranges are required, the three-dimensional color solid is divided into smaller, non-overlapping range volumes.

Reference is now made back to Fig. 1. As is known in the art, the sharp signal generator 10 separately performs edge detection and edge signal generation from each of the color separation signals R, G and B. To each detected edge in each of the color separations, it increases the brightness

content of the bright side of the edge and decreases the content of the darker side of the edge. Generally, the steeper the edge, the greater the increase and decrease in the color content of the two sides of the edge.

It will be appreciated that the present invention minimally requires the generation of two sharp signals. Typically, the red and green sharp signals, R_s and G_s are generated and one of them is additionally input to switch 24. Furthermore, in color separation sources which utilize the C, M, Y and K color separations to detect edges, the sharp signal generator 10 can generate four sharp signals.

Reference is now made to Fig. 2 which illustrates a further embodiment of the present invention. In this embodiment, the switches 20, 22 and 24 are replaced by edge selectors 40, 42 and 44, respectively. In response to the range in which a given pixel is found, the color coordinates computer 30 indicates to each edge selector 40, 42 and 44 which sharp signal R_s , G_s or B_s to select, thereby allowing for 27 different modes of connecting the sharp signals to the channels. Typically, there are defined 27 or fewer volume ranges of the color solid to match the 27 different modes. It will be appreciated that the collection of sharp signals to be connected to the channels can include all of one sharp signal or one of each signal or some other collection.

A more gradual change between any two sharpening modes can be implemented with an alternative division of the Solid 30 as shown in Fig. 4. Three new radii r_a and r_b and r_1 along the luminance axis are defined as follows:

$$0 \leq r_a \leq r_0 \quad (1)$$

$$r_0 < r_b \leq r_1 \quad (2)$$

and r_1 is the outer radius of the Solid 30.

For only two modes, the area with radii of less than r_0 typically defines a first mode and the area with radii between r_0 and r_1 defines a second mode. For example, the first mode might be that all color separation signals R, G and B receive the sharp signal G_s . The second mode might be that each color separation R, G or B receives its corresponding sharp signal, R_s , G_s or B_s .

In accordance with this alternative embodiment of the present invention, a gradual change between the two modes can be produced as follows.

If the color of a pixel has a radius r which falls within the area of the Solid 30 between 0 and r_a , the first mode is operative. If the radius r falls within the area of the Solid 30 between r_b and r_1 , the second mode is operative. If the radius r falls within the area of the Solid 30 between r_a and r_b , the color separations R, G and B receive a first percentage of the sharp signals R_s , G_s and B_s they

receive in the first mode and a second percentage of the sharp signals they receive in the second mode, where the first percentage is defined by how close the radius r is to r_a and the second percentage is defined by how close the radius is to r_b . The sum of the first and second percentages is equal to 1.

For the modes mentioned hereinabove, example sharp signals are as follows, where the symbol $\leq$ indicates reception.

$$R \leq R_a^*(a/c) + G_a^*(b/c) \quad (3)$$

$$G \leq G_a^*(a/c) + G_b^*(b/c) \quad (4)$$

$$B \leq B_a^*(a/c) + G_b^*(b/c) \quad (5)$$

where

$$a = (r - r_a) \quad (6)$$

$$b = (r_b - r) \quad (7)$$

$$c = (r_b - r_a) \quad (8)$$

It will be noted that the Green color separation receives G_a in both modes for this example.

In this example, as the radius r approaches r_b , the sharp signals received resemble the sharp signals received in the second mode. On the other hand, for radii r close to r_a , the sharp signals received resemble the sharp signals received in the first mode.

It will be appreciated that the present invention can be realized in analog or digital electronic hardware or in software operating on a suitable computer, such as an IBM PC.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather the scope of the present invention is defined only by the claims which follow:

Claims

1. Apparatus for sharpening a color image having a multiplicity of color separation signals defining a plurality of color pixels comprising:
 - means for generating at least two sharpening signals from said color separation signals; and
 - means for combining each of said color separation signals with any collection of said at least two sharpening signals, wherein said collection changes throughout said color image.
2. Apparatus according to claim 1 and wherein said means for combining include means for determining said collection as a function of at least one dimension of the at least three dimensional color value of each of said plurality of pixels.
3. Apparatus according to claim 2 and wherein said means for determining include means for separating a color solid into first, second and third volumes wherein if said three dimensional color value of a pixel falls within said first volume, a first collection of sharpening signals are combined with said color separation signals, if said three dimensional color value of a pixel falls within said third volume a second collection of sharpening signals are combined with said color separation signals and if said three dimensional color value of a pixel falls within said second volume, located generally between said first and third volumes, a combination of said first and said second collections of sharpening signals are combined with said color separation signals wherein said combination gradually changes from generally the entirety of said first collection to generally the entirety of said second collection.
4. Apparatus according to any of the previous claims and wherein said means for generating include means for performing edge detection on each of said color separation signals.
5. Apparatus according to any of the previous claims and wherein said color separation signals are in a predetermined color space and said sharpening signals are also in said predetermined color space.
6. A method of sharpening a color image having a multiplicity of color separation signals defining a plurality of color pixels including the steps of:
 - generating at least two sharpening signals from said color separation signals; and
 - combining each of said color separation signals with any collection of said at least two sharpening signals wherein said collection changes throughout said color image.
7. Method according to claim 6 and wherein said step of combining includes the step of determining said collection as a function of at least one dimension of the at least three dimensional color value of each of said plurality of pixels.
8. Method according to claim 7 and wherein said step of determining includes the step of separating a color solid into first, second and third volumes wherein if said three dimensional color value of a pixel falls within said first volume, a first collection of sharpening signals are combined with said color separation signals, if said three dimensional color value of a pixel

falls within said third volume a second collection of sharpening signals are combined with said color separation signals and if said three dimensional color value of a pixel falls within said second volume, located generally between said first and third volumes, a combination of said first and said second collections of sharpening signals are combined with said color separation signals wherein said combination gradually changes from generally the entirety of said first collection to generally the entirety of said second collection.

9. Method according to any of the previous claims 6 - 7 and wherein said step of generating includes the step of performing edge detection on each of said color separation signals.

5

10

15

20

25

30

35


40

45

50

55

6






FIG. 3




FIG. 4

